

Product No: ISDA100344R1

ABB XT 5N 400 TMA 320-3200 3P F F ISDA100344R1

FEATURES

- Fixed Three Pole
- Front Terminals
- Thermo-magnetic release
- ABB EcoSolutions



General Information	
Brand	ABB
Product Type	MCCB
Version	Fixed
Technical Attributes	
Design of Control Element	Toggle
Breaking Capacity 415V AC - Icu (kA)	36
I - Short-circuit Current Setting I3 (A)	1600 - 3200
L - Overload Current Setting I1 (A)	224 - 320
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Front Side
No. of Poles	3
Overload Release Current Setting (A)	128
Power Loss (W)	16.9
Rated Current (A)	320
Rated Frequency (Hz)	50/60
Rated Instantaneous Short-Circuit Current - Ii (A)	1600
Rated Insulation Voltage (V)	1000
Rated Uninterrupted Current - Iu (A)	400
Rated Voltage (V)	690
Trip Unit	TMA



Dimensions

Dimensions (mm)	140W x 205H x 103.5D
-----------------	----------------------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	IEC 60947-2
-------------------------	-------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------