



ECOLINE EMERGENCY SL9732TC/DP3EM - 10/50W

MAINTAINED OR NON-MAINTAINED - Compliant to AS/NZS 2293, narrow body profile

Application

Perfect for interior commercial emergency lighting installations

Design Specifications

- Narrow steel body (65mm) body profile, white powder coat finish
- LiFePO4 battery technology for long life
- Designed for both maintained and non-maintained systems
- Selectable CCT 3000K / 4000K / 5700K
- Selectable maintained power
- LED charge status display and test switch, guaranteed 90 minutes emergency function Note: 20EM = D50C0, D32@C90, 40EM = D50@C0, D32@C90 emergency classification



Model	Power (W)	Beam Angle (°)	Life (hrs)	Temp (°C)	Weight (kg)
SL9732/20TC/DP3EM	20	120	100,000	40	0.1
SL9732/40TC/DP3EM	40	120	100,000	40	0.2
SL9732/50TC/DP3EM	50	120	100,000	40	0.3



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Dimmable
	SL9732/20TC/DP3EM	240	10/20	2370/2600/2460	3000/4000/5700	NO
	SL9732/40TC/DP3EM	240	20/40	4600/5100/4860	3000/4000/5700	NO
	SL9732/50TC/DP3EM	240	25/50	6100/6700/6300	3000/4000/5700	NO

CRI	Beam Angle (°)	Body Colour	Dim (mm)	Mass (kg)
80	120	WHITE	600(L) x 65(W) x 65(H)	1
80	120	WHITE	1135(L) x 65(W) x 65(H)	1.33
80	120	WHITE	1455(L) x 65(W) x 65(H)	1.72


Important notes: (1) Battery warranty twelve (12) months (2) In the interest of transport and safety, emergency products are

supplied with the battery disconnected. (3) In addition to specific emergency commissioning instructions, the battery MUST be connected at the time of installation. (4) Continual use in emergency mode greater than 240 hours without recharge, will result in battery failure and void battery warranty (5) Lumens (lm) displayed are at full maintained power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL9732 40



SL9732 20

