

DATA SHEET

ACCESSORY


















MODEL: RWB2

Key Information

Product or component Device application

Colour Quantity Packaging Type Wireless Base Mounting with Cable or Conduit White Carton



Power Supply	AC Mains	
Rated Supply Voltage	220240Vac	
Battery Life	10 YR	
Backup Type	Non-replaceable 3V Lithium Battery	
Operating Current	< 40mA	
Radio Frequency	433.92 MHz	
Number of Device	Wired Interconnect up to 40 Pieces	
	Wireless Interconnect up to 20 Pieces	
Operating Distance Hard Wired Interconnected	150M in Free Field	
Operating Distance Wireless Interconnected	30M Indoor Use Line of Sight	
	100M in Free Field	
Remote Control	Red Smoke Alarms Model RAC	
Type of Installation	Indoor	
Connections - Terminals	For Active:	2 x 1.5 MM² wiring capacity
	For Neutral:	2 x 1.5 MM² wiring capacity
	For Earth Loop:	2 x 1.5 MM ² wiring capacity
	For Interconnect:	2 x 1.5 MM² wiring capacity
Visual Indicators	Red LED for Pairing, Warning and Low Battery	
Type of Installation	Indoor	
Diameter	140 MM	
Knockouts	Two Side Knockouts for Conduit Surface Mount	
	One Internal Knockout for Ceiling Mount	
Ambient Air Temperature	045°C	
for Operation	····	
Relative Humidity	595%	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



RF Pairing Button