



Bondi (non-emergency)

600mm Double Diffused/Wireguard Batten

The Bondi series LED batten lights are the perfect solution for projects and economic applications, utilising a replaceable Kwicky module for unparalleled ease of maintenance. Optional Beacon Bondi motion sensor available for a range of lighting-control and energy-saving applications.





Features

-  2,000 Lumens
-  Tri-Colour

Accessories

- Motion Sensor: SENSOR-BONDI
- Wireless Motion Sensor: BEACON-BONDI
- Replacement Diffuser: DIFF-1200-BONDI
- Replacement Wireguard: WIRE-1200-BONDI

Ordering Codes

-  BONDI-600-2-D
-  BONDI-600-2-W



Download the Elumen app



elumen.com.au
1300 927 533

Device Specifications

OPERATIONAL INFORMATION	
VOLTAGE	220 - 240VAC
FREQUENCY	50Hz
LUMINOUS FLUX	2000lm (Wireguard) 1950lm (Diffused)
POWER CONSUMPTION	21W
AMBIENT TEMPERATURE	1°C - 40°C
IP RATING	IP20
COLOUR TEMPERATURE	3000K / 4000K / 5000K
MOUNTING TYPE	Surface Ceiling Mount
OPERATING MODE	Switch Controlled
PROJECTED LED LIGHT SOURCE LIFE	100,000 Hours

CONSTRUCTION, DIMENSIONS AND WEIGHT	
CONSTRUCTION	White Powder Coated Steel Body, Polycarbonate Diffuser
WEIGHT	1.7kg
CARTON QTY	4
CARTON DIMENSIONS	640mm x 280mm x 210mm
CARTON WEIGHT	7.5kg

COMPLIANCE AND TESTING	
STANDARDS	AS/NZS 60598.2.22 AS/NZS CISPR 15

Product Drawing

