

## Product data sheet Characteristics

# EVH5A11N2C5

Charging station, Schneider Charge, 3P+N, attached cable 5m, 11kW, 16A





Main	
Range	Schneider Charge
Product name	Schneider Charge
Product or component type	Charging station
Poles description	3P + N
Mounting mode	Wall-mounted
Max power	11 kW 16 A
Number of charge point	1
Connection to the	Attached cable T2 bottom 5 m

### Complementary

Rated supply voltage	400 V AC 5060 Hz +/- 10 %	
Earthing system	IT 230	
	TT	
	TN-S	
Number of inputs	1	
Input type	Dry contact for dynamic energy management	
Local signalling	Red, green and blue 1 LED, function: status indication	
Protection type	Earth-leakage protection	
Height	352 mm	
Width	244 mm	
Depth	117 mm	
Net weight	4.4 kg	
Colour	White/green	
Standards	EN 61851	
	IEC 61851-1	
Communication network type	Wi-Fi	
	Wireless	
	Ethernet	
Communication port protocol	OCPP 1.6, for connection to the Schneider Electric Wiser app	

#### Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
IK degree of protection	IK10
Ambient air temperature for operation	-3055 °C
Ambient air temperature for storage	-4085 °C
Relative humidity	595 %
Operating altitude	02000 m

## Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	35.000 cm
Package 1 Length	50.000 cm
Package 1 Weight	618.000 g
Unit Type of Package 2	P12
Number of Units in Package 2	18
Package 2 Height	103.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	137.000 kg

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	<sup>☑</sup> End Of Life Information	

Life Is On