

Transparent industrial silicone sealant 300 ml



Characteristics

Reference : **BIZ 711 560**

Colour : **Transparent**

Volume (ml) : **300**

Benefits

- High performance.
- Permanent elasticity.
- Multifunctional: versatile adhesive and sealant.
- Impervious to rain, snow, extreme temperature changes or constant exposure to ultraviolet light (UV).
- Watertight.
- Weak odour.
- Superior adhesion properties.
- Fast drying time.



GENERAL INFORMATION

Description

Bizline silicone is a high-quality, single-component, neutral silicone sealant.

Technical details

Temperature resistance (°C): -62 to +177.

Application temperature (°C): 10 to 60.

Skin formation time (min): 6.

Curing speed (days): 5 to 7 (to a depth of 10 mm at 23°C and 50% relative humidity).

Advices

Cannot be painted.

Do not apply to wet surfaces.

Do not use on extruded polycarbonates or polyacrylates if they are tensioned.

Not recommended for concrete.

Not recommended for marble, granite or stone.

Life span

18 months

Application(s)

Watertight seals between glass and aluminium.

Perimeter seals between aluminium window frames, brickwork and masonry.

Airtight seals in concrete panels.

General construction, electrical, marine, industrial and maintenance applications.

Suitable for interior and exterior use.

Instructions

1. The surface must be clean, dry and free of wax, oils, grease or any loose or flaking paint.
2. Use masking tape to ensure clean work.
3. Ensure that the depth of the sealant does not exceed 10 mm (use a support material such as polyurethane foam if necessary).
4. Apply the sealant using a caulking gun.
5. Smooth before skinning (within 10 minutes) and immediately remove excess sealant with a cloth dampened with mineral turpentine. If used, remove masking tape immediately.



LOGISTIC INFORMATION

Packaging



Cartridge

Height (cm) : 23

Longueur (cm) : 4,8

Depth (cm) : 4,8

Net weight (kg) : 0,3

Gross weight (kg) : 310



3 701395 164939

Outer package 1



Carton box

Height (cm) : 24,5

Longueur (cm) : 25

Depth (cm) : 20

Gross weight (kg) : 7,6

x 20

Outer package 2



Pallet

Height (cm) : 115

Longueur (cm) : 100

Depth (cm) : 100

Gross weight (kg) : 571

x 1 600