

# Blue PVC adhesive 125 ml for pipes, fittings and plates

## Characteristics

: 1280



## GENERAL INFORMATION

### Description

Resin-based adhesive specially formulated for bonding PVC-U pipes and fittings.

### Technical details

Viscosity: medium bodied.

Composition: solvent.

Application temperature (°C): 10 to 30, away from direct sunlight.

### Advices

Make sure you wear the appropriate personal protection equipment when using the solvent cement/priming liquid.

DO NOT mix additives with the priming fluid or the pipe glue.

Do not use gelled or lumpy glue. It must have the consistency of a syrup.

When not in use, secure the lid on the bottles.

### Life span

24 months

### Application(s)

For joining PVC-U conduits in electrical applications.

Gluing of PVC-U sheets.

### Instructions

#### 1. Preparing the seal:

2. Make sure the pipe is cut at right angles and clean off any burrs.
3. To ensure correct assembly of the seal, mark the pipe at a distance equal to the depth of the cavity.
4. Test the seals and adjust.
5. Clean the pipe and the cavity interior (essential to ensure a strong seal).

#### Make the seal:

6. Shake the product vigorously before use.
7. Apply the product evenly to both surfaces, first to the interior, then to the exterior of the pipe.
8. Apply pressure.
9. Maintain pressure for at least 1 minute.
10. Do not touch for 5 minutes.
11. Maximum adhesion after 24 hours.

## TECHNICAL DOCUMENT(S)

### Technical documentation available on our website :



SDS




## LOGISTIC INFORMATION

 Packaging**Plastic bottle**

Height (cm) : 7,5

Longueur (cm) : 6

Depth (cm) : 6

 Net weight (kg) : 0,125 Gross weight (kg) : 0,15 Outer package 1


x 18

**Carton box**

Height (cm) : 165

Longueur (cm) : 20

Depth (cm) : 19,5

 Gross weight (kg) : 2,8 Outer package 2

x 3 240

**Pallet**

Height (cm) : 113

Longueur (cm) : 123

Depth (cm) : 102

 Gross weight (kg) : 530