



# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

## Section 1: Identification: Product identifier and chemical identity

### Product identifier

**Product Name** BizLine Clear PVC Jointing Cement

**Product Code(s)**  
BIZ400273 Clear PVC Jointing Cement 125 mL  
BIZ400274 Clear PVC Jointing Cement 250 mL  
BIZ400275 Clear PVC Jointing Cement 500 mL

### Other means of identification

**Proper shipping name** Adhesives

**UN number or ID number** UN1133

**Pure substance/mixture** Mixture

### Recommended use of the chemical and restrictions on use

**Recommended use** Adhesives

**Uses advised against** Consumer use.

### Details of manufacturer or importer

#### Supplier

Rexel Australia  
Level 2, Building 1/3 Richardson Place,  
North Ryde NSW 2113  
Australia  
Tel: +612 (02) 9887 6222

**ABN:** 42 000 437 758

### Emergency telephone number

Emergency telephone number Poisons Information Centre, Australia: 13 11 26

## Section 2: Hazard(s) identification

### GHS Classification

|   |                           |
|---|---------------------------|
| <b>Flammable liquids</b>                                | Category 2 - (H225)       |
| <b>Skin corrosion/irritation</b>                        | Category 2 - (H315)       |
| <b>Serious eye damage/eye irritation</b>                | Category 1 - (H318)       |
| <b>Specific target organ toxicity (single exposure)</b> | Category 3 - (H335, H336) |

### Label elements

Flame  
Exclamation mark  
Corrosion

# SAFETY DATA SHEET

**BizLine Clear PVC Jointing Cement**  
**Revision Number 1**

**Revision date** 11-Jul-2024  
**Supersedes date** 11-Jul-2024



**Signal word**  
DANGER

## **Hazard statements**

H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
Repeated exposure may cause skin dryness or cracking

## **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Ground and bond container and receiving equipment  
Use non-sparking tools  
Take action to prevent static discharges  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Wear protective gloves/clothing and eye/face protection  
Keep cool  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor  
IF ON SKIN: Wash with plenty of water and soap  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Call a POISON CENTER or doctor if you feel unwell  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

## **Precautionary Statements - Storage**

Store in a well-ventilated place

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## **Other hazards which do not result in classification**

May be harmful in contact with skin.  
In use, may form flammable/explosive vapor-air mixture.

## **Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)**

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

**Poison Schedule Number** 5

## **Label requirements in accordance with SUSMP**

CAUTION  
KEEP OUT OF REACH OF CHILDREN  
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

## **Section 3: Composition and information on ingredients, in accordance with Schedule 8**

## **Substance**

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

Not applicable

## Mixture

| Chemical name                           | CAS No.     | Weight-% |
|---|-------------|----------|
| Methyl ethyl ketone                     | 78-93-3     | 15 - 40  |
| Cyclohexanone                           | 108-94-1    | 10 - 30  |
| Acetone                                 | 67-64-1     | 10 - 30  |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3   | 0.1 - 1  |
| Non-hazardous ingredients               | Proprietary | Balance  |

## **Section 4: First aid measures**

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26  
Poisons Information Center, New Zealand: 0800 764 766

### Description of first aid measures

**General advice** Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

**Inhalation** Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical attention. Remove contact lenses, if present and easy to do. Continue rinsing.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

### Most important symptoms and effects, both acute and delayed

**Symptoms** Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## **Section 5: Firefighting measures**

### Suitable Extinguishing Media

**Suitable extinguishing media** Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** No information available.

### Specific hazards arising from the chemical

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO<sub>2</sub>). Hydrogen chloride. Hydrochloric Acid.

## Special protective actions for fire-fighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## Section 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Keep from any possible contact with water. Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

### Precautions to prevent secondary hazards

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## Section 7: Handling and storage, including how the chemical may be safely used

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

## Conditions for safe storage, including any incompatibilities

### Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Keep away from water or moist air.

### Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

## Section 8: Exposure controls and personal protection

### Control parameters

### Exposure Limits

| Chemical name                  | Australia   |
|--------------------------------|---|
| Methyl ethyl ketone<br>78-93-3 | TWA: 150 ppm<br>TWA: 445 mg/m <sup>3</sup><br>STEL: 300 ppm<br>STEL: 890 mg/m <sup>3</sup>    |
| Cyclohexanone<br>108-94-1      | TWA: 25 ppm<br>TWA: 100 mg/m <sup>3</sup>   |
| Acetone<br>67-64-1             | TWA: 500 ppm<br>TWA: 1185 mg/m <sup>3</sup><br>STEL: 1000 ppm<br>STEL: 2375 mg/m <sup>3</sup> |

OEL as published by Safe Work Australia

### Biological occupational exposure limits

### Appropriate engineering controls

### Engineering controls

Showers, eyewash stations, and ventilation systems.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Tight sealing safety goggles.

### Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

### Hand protection

Wear suitable gloves. Impervious gloves.

### Respiratory protection

Organic gases and vapors filter conforming to EN 14387.

### Environmental exposure controls

No information available.

## Section 9: Physical and chemical properties

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

## Information on basic physical and chemical properties

|                |                          |
|----------------|--------------------------|
| Physical state | Liquid                   |
| Appearance     | Liquid                   |
| Color          | Clear, colorless         |
| Odor           | Ketone                   |
| Odor threshold | No information available |

| Property                                | Values                               | Remarks • Method                  |
|---|--------------------------------------|-----------------------------------|
| pH                                      | No data available                    | Not applicable Insoluble in water |
| pH (as aqueous solution)                | No data available                    |                                   |
| Melting point / freezing point          | No data available                    |                                   |
| Initial boiling point and boiling range | 56 °C                                |                                   |
| Flash point                             | -4 °C                                | (Methyl Ethyl Ketone)             |
| Evaporation rate                        | No data available                    |                                   |
| Flammability                            | No data available                    | Flammable liquid                  |
| Flammability Limit in Air               |                                      |                                   |
| Upper flammability or explosive limits  | 11.5                                 |                                   |
| Lower flammability or explosive limits  | 1.8                                  |                                   |
| Vapor pressure                          | 9500                                 |                                   |
| Relative vapor density                  | > 1                                  |                                   |
| Relative density                        | 0.94                                 |                                   |
| Water solubility                        | Partially soluble                    |                                   |
| Solubility(ies)                         | No data available                    |                                   |
| Partition coefficient                   | No data available                    |                                   |
| Autoignition temperature                | 515 °C                               |                                   |
| Decomposition temperature               | No data available                    |                                   |
| Kinematic viscosity                     | No data available mm <sup>2</sup> /s |                                   |
| Dynamic viscosity                       | approx 600 - 900 mPa s               |                                   |
| Explosive properties                    | No information available             |                                   |
| Oxidizing properties                    | No information available             |                                   |

### Other information

|                   |                          |
|-------------------|--------------------------|
| Solid content (%) | approx 21.5              |
| Liquid Density    | No information available |
| VOC content       | 732 g/L                  |

## Section 10: Stability and reactivity

### Reactivity

|            |                           |
|------------|---------------------------|
| Reactivity | No information available. |
|------------|---------------------------|

### Chemical stability

|           |                                   |
|-----------|-----------------------------------|
| Stability | Unstable on exposure to moisture. |
|-----------|-----------------------------------|

### Explosion data

|                                  |       |
|----------------------------------|-------|
| Sensitivity to mechanical impact | None. |
| Sensitivity to static discharge  | Yes.  |

### Possibility of hazardous reactions

|                                    |                               |
|------------------------------------|-------------------------------|
| Possibility of hazardous reactions | None under normal processing. |
|------------------------------------|-------------------------------|

### Conditions to avoid

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

**Conditions to avoid** Heat, flames and sparks. Keep from any possible contact with water.

## Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

## Hazardous decomposition products

**Hazardous decomposition products** Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## **Section 11: TOXICOLOGICAL INFORMATION**

### Acute toxicity

### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.

**Skin contact** Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Symptoms** Redness. Burning. May cause blindness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 6,049.40  
ATEmix (dermal) 4,335.00  
ATEmix (inhalation-gas) >20000  
ATEmix (inhalation-vapor) 43.40  
ATEmix (inhalation-dust/mist) >5

### Component Information

| Chemical name                           | Oral LD50                                  | Dermal LD50                          | Inhalation LC50         |
|---|--|--------------------------------------|-------------------------|
| Methyl ethyl ketone                     | =2483 mg/kg (Rattus)                       | = 5000 mg/kg (Oryctolagus cuniculus) | =11700 ppm (Rattus) 4 h |
| Cyclohexanone                           | =1535 mg/kg (Rattus)                       | = 947 mg/kg (Oryctolagus cuniculus)  | =8000 ppm (Rattus) 4 h  |
| Acetone                                 | =5800 mg/kg (Rattus)<br>3000 mg/Kg (mouse) | >15800 mg/Kg (Rattus)                | =79 mg/l(Rattus) 4 h    |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | =11300 µL/kg (Rattus)                      | LD50 >2000 mg/Kg (Rattus)            | -                       |

See section 16 for terms and abbreviations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

| Component Information                                   |         |                |                |               |          |
|---|---------|----------------|----------------|---------------|----------|
| Methyl ethyl ketone (78-93-3)                           |         |                |                |               |          |
| Method  | Species | Exposure route | Effective dose | Exposure time | Results  |
| OECD Test No. 405:<br>Acute Eye<br>Irritation/Corrosion | Rabbit  | eye            |                |               | irritant |

| Acetone (67-64-1)                                       |         |                |                |               |          |
|---|---------|----------------|----------------|---------------|----------|
| Method  | Species | Exposure route | Effective dose | Exposure time | Results  |
| OECD Test No. 405:<br>Acute Eye<br>Irritation/Corrosion | Rabbit  | eye            |                |               | irritant |

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

## Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name  | Australia | European Union | IARC    |
|--|-----------|----------------|---------|
| Cyclohexanone<br>108-94-1                            |           |                | Group 3 |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane<br>1675-54-3 |           |                | Group 3 |

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## Section 12: Ecological information

### Ecotoxicity

#### Aquatic ecotoxicity

| Chemical name       | Algae/aquatic plants | Fish                  | Toxicity to microorganisms | Crustacea            |
|---------------------|----------------------|-----------------------|----------------------------|----------------------|
| Methyl ethyl ketone | EC50=1972 mg/l       | LC50: 3130 - 3320mg/L | EC50 = 3403 mg/L 30        | EC50 48 h > 308 mg/L |



# SAFETY DATA SHEET

**BizLine Clear PVC Jointing Cement**  
Revision Number 1

**Revision date** 11-Jul-2024  
**Supersedes date** 11-Jul-2024

|  |  |   |   |   |
|--|--|---|---|---|
| 78-93-3  | (Pseudokirchneriella subcapitata)                                  | (96h, Pimephales promelas)                                  | min<br>EC50 = 3426 mg/L 5 min   | (Daphnia magna )                                    |
| Cyclohexanone<br>108-94-1                            | EC50: =20mg/L (96h, Chlorella vulgaris)                            | LC50 96 h 481 - 578 mg/L (Pimephales promelas flow-through) | EC50 = 18.5 mg/L 5 min<br>EC50 = 21.3 mg/L 10 min<br>EC50 = 25 mg/L 5 min | EC50: =800mg/L (24h, Daphnia magna)                 |
| Acetone<br>67-64-1                                   | -  | LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )           | EC50 = 14500 mg/L 15 min  | EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static) |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane<br>1675-54-3 | EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009 | 1.5 mg/l 96Hr (Oncorhynchus mykiss) (OECD 203)              | -   | LD50 (48h) =2.7 mg/L (Daphnia magna) (OECD 202)     |

## Persistence and degradability

**Persistence and degradability** No information available.

| Component Information   |               |                |                            |
|---|---------------|----------------|----------------------------|
| Methyl ethyl ketone (78-93-3)   |               |                |                            |
| Method  | Exposure time | Value          | Results                    |
| OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D) | 28 days       | biodegradation | 98 % Readily biodegradable |

  

| Acetone (67-64-1)   |               |                |                            |
|---|---------------|----------------|----------------------------|
| Method  | Exposure time | Value          | Results                    |
| OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B) | 28 days       | biodegradation | 91 % Readily biodegradable |

## Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

| Chemical name  | Partition coefficient |
|--|-----------------------|
| Methyl ethyl ketone<br>78-93-3                       | 0.3                   |
| Cyclohexanone<br>108-94-1                            | 0.86                  |
| Acetone<br>67-64-1                                   | -0.24                 |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane<br>1675-54-3 | 3.78                  |

## Mobility

**Mobility in soil** No information available.

**Mobility** No information available.

## Other adverse effects

**Other adverse effects** No information available.

# SAFETY DATA SHEET

BizLine Clear PVC Jointing Cement  
Revision Number 1

Revision date 11-Jul-2024  
Supersedes date 11-Jul-2024

## Section 13: Disposal considerations

### Disposal methods

|                                     |  |
|-------------------------------------|--|
| Waste from residues/unused products | Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation. |
| Contaminated packaging              | Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.  |

## Section 14: Transport information

### ADG

|                            |                          |
|----------------------------|--------------------------|
| UN number or ID number     | UN1133                   |
| UN proper shipping name    | Adhesives                |
| Transport hazard class(es) | 3                        |
| Packing group              | II                       |
| Environmental hazard       | No                       |
| Limited quantity (LQ)      | 5 L                      |
| Description                | UN1133, Adhesives, 3, II |
| Hazchem code               | •3YE                     |

### IATA

|                            |                          |
|----------------------------|--------------------------|
| UN number or ID number     | UN1133                   |
| Transport hazard class(es) | 3                        |
| Packing group              | II                       |
| ERG Code                   | 3L                       |
| Special Provisions         | A3                       |
| Limited quantity (LQ)      | 1 L                      |
| Description                | UN1133, Adhesives, 3, II |

### IMDG

|                            |                                       |
|----------------------------|---------------------------------------|
| UN number or ID number     | UN1133                                |
| Transport hazard class(es) | 3                                     |
| Packing group              | II                                    |
| EmS-No.                    | F-E, S-D                              |
| Limited Quantity (LQ)      | 5 L                                   |
| Marine pollutant           | NP                                    |
| Description                | UN1133, Adhesives, 3, II, (-4°C c.c.) |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
No information available

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

##### Australia

See section 8 for national exposure control parameters

#### Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

#### Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

# SAFETY DATA SHEET

**BizLine Clear PVC Jointing Cement**  
Revision Number 1

**Revision date** 11-Jul-2024  
**Supersedes date** 11-Jul-2024

## Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III

Liquids with flash points <61°C kept above their boiling points at ambient conditions

Threshold quantity (T)

50 000

200

## National pollutant inventory

Subject to reporting requirement

| Chemical name                  | National pollutant inventory  |
|--------------------------------|---|
| Methyl ethyl ketone<br>78-93-3 | 10 tonne/yr Threshold category 1  |
| Cyclohexanone<br>108-94-1      | 20 MW Threshold category 2b total<br>60000 MWH Threshold category 2b total<br>1 tonne/h Threshold category 2a total<br>25 tonne/yr Threshold category 1a total<br>400 tonne/yr Threshold category 2a total<br>2000 tonne/yr Threshold category 2b total |
| Acetone<br>67-64-1             | 10 tonne/yr Threshold category 1  |

## International Inventories

|              |          |
|--------------|----------|
| <b>AIIC</b>  | Complies |
| <b>NZIoC</b> | Complies |
| <b>ENCS</b>  | Complies |
| <b>IECSC</b> | Complies |
| <b>KECI</b>  | Complies |
| <b>PICCS</b> | Complies |

### Legend:

**AIIC** - Australian Inventory of Industrial Chemicals

**NZIoC** - New Zealand Inventory of Chemicals

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

## International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

## Europe

**Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)**

### SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

**Directive 2011/65/EU (EU RoHS 2), as amended by the Delegated Directive (EU) 2015/863 (EU RoHS 3)**

# SAFETY DATA SHEET

**BizLine Clear PVC Jointing Cement**  
Revision Number 1

**Revision date** 11-Jul-2024  
**Supersedes date** 11-Jul-2024

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

## Section 16: Any other relevant information

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 11-Jul-2024

### Revision Note

\*\*\*Indicates updated data since last publication.

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

|         |                             |      |                                  |
|---------|-----------------------------|------|----------------------------------|
| TWA     | TWA (time-weighted average) | STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value         | Sk*  | Skin designation                 |
| C       | Carcinogen                  |      |                                  |

#### Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

#### Section 12: Ecological information

EC50 (effective concentration)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**