Product datasheet

Specifications



Overview

Lead time

Special Order - Call for Quoted Lead Times

Condensate pump

ACAC10039

Main

 Main Input Voltage
 200...240 V

 Provided equipment
 User manual

 Physical
 V

| Height | 8.5 cm |
|---------------------|--------------------|
| Width | 8.65 cm |
| Depth | 27.64 cm |
| Net weight | 1.8 kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |

Input

Network frequency

50 Hz

Packing Units

| • | |
|------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 13 cm |
| Package 1 Width | 12 cm |
| Package 1 Length | 39 cm |
| Package 1 Weight | 2 kg |

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Use Better

| ℬ Materials and Substances | | | |
|--|--|--|--|
| Packaging made with recycled cardboard | No | | |
| Packaging without single use plastic | No | | |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope | | |
| Use Again | | | |

| $^{igodoldolde{U}}$ Repack and remanufacture | | |
|--|----|--|
| Take-back | No | |