Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



APC 5kVA and 6kVA Marine Filter Rack-Mount



SRT6RMM

Overview

Presentation

Troomaton	applications.		
Lead time	Usually in Stock		
Main			
Main Input Voltage	200 V		
	208 V		
	220 V		
	230 V		
	240 V		
Product or component type	Filter		
Main Output Voltage	200 V		
	208 V		
	220 V		
	230 V		
	240 V		
Other Output Voltage	208 V		
	220 V		
	230 V		
	240 V		
Output connector type	Hard wire 3-wire (H N + E) 1		
Connections - terminals	2 screw terminal		
Number of rack unit	1U		
Provided equipment	Installation guide		
	Mounting hardware		
	Rack mounting brackets		
	User manual		

Environment

Ambient air temperature for operation	055 °C	
Relative humidity	095 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2575 °C	
Storage Relative Humidity	095 %	
Storage altitude	0.000000000015240.0000000000 m	

Physical

Colour	Black
Height	4.4 cm

Width	48.3 cm	
Depth	33 cm	
Net weight	6.73 kg	
Mounting location	Front	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Mounting position	Horizontal	

Input

Network frequency	4565 Hz	
[In] rated current	50 A	
Number of input connectors	1 hard wire 3-wire	
Permissible voltage	100240 V	
Max line current	50 A	
Input current limits	50 A	
Load capacity	6000 VA	

Output

Max current draw 50 A

Conformance

Product certifications DNV

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	40.6 cm
Package 1 Length	55.9 cm
Package 1 Weight	8.27 kg

Contractual warranty

Warranty 2 year (manufacturer's defect)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

EU RoHS Directive

Compliant with Exemptions

REACh Regulation

REACh Declaration

W Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

O	Repack	and	remanufacture
---	--------	-----	---------------

Circularity Profile End of Life Information

Take-back Yes