

Product datasheet

Specifications



CDU Flexible Fluid Piping - 300 Feet (91.4 Meters)

ACAC20002

Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

General

Provided equipment	Installation guide
Maximum recommended flowrate	1.2 l/s
Tube material	PEX-AL-PEX
Pressure sensor size	1034.2 kPa
Fluid connection type	Unterminated
Minimum bending radius	203.2 mm
Minimum fluid temperature	42 °F
Maximum fluid temperature	60 °F
Pressure drop per foot	1.28 kPa @ 0.88 l/s

Physical

Length	91.4 m
Colour	White
Depth	106.7 cm
Height	27.9 cm
Net weight	37.73 kg
Width	106.7 cm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.8 cm
Package 1 Width	115.6 cm
Package 1 Length	115.6 cm
Package 1 Weight	39.55 kg
Number of Units in Package 3	6

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Use Again

Repack and remanufacture	
Take-back	No