

Product datasheet

Specifications



Condenser, 46kw, 95F/115F(35C/46C),230V/1, 50Hz, with CE

ACCD75232-C

Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

Main

Main Input Voltage	230 V
--------------------	-------

General

Air discharge option	Horizontal Upflow
air flow	5191.4 l/s
Inrush current	6 A

Physical

Height	134.4 cm
Width	111 cm
Depth	209 cm
Net weight	135 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Length	2.090 m

Input

Network frequency	50 Hz
-------------------	-------

Conformance

Product certifications	CE
------------------------	----

Environmental

Ambient air temperature for operation	-20...50 °C
Operating altitude	0...10000 ft
Audible noise at 1 meter from surface of unit	56.6 dBA

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	139.7 cm
Package 1 Width	228.6 cm
Package 1 Length	127 cm
Package 1 Weight	150 kg

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Use Again

Repack and remanufacture	
Take-back	No