

Product datasheet

Specifications



Easy Rack PDU, Metered Outlet,
0U, 1 Phase, 3.7kW, 230V, 16A,
20 C13 and 4 C19 outlets,
IEC60309 2P + E inlet

EPDU1116SMBO

⚠ To be discontinued

⚠ Discontinued on: 1 Sept 2024

⚠ To be end-of-service on: 21 May 2026

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Metered outlet
Cord length	3 m
Number of cables	1
Provided equipment	Installation guide Safety guide Rack mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	1800 mm
Width	55 mm
Output Voltage	230 V
Depth	56 mm
Net weight	6.67 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 2P + E
Mounting mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP
[In] rated current	16 A
Permissible voltage	200...240 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19
Communication network type	10/100BASE-T

Environment

Product certifications	CE EAC TÜV RCM UKCA
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15000 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2030 mm
Package 1 Width	195 mm
Package 1 Length	130 mm
Package 1 Weight	7.84 kg





Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

<div>Environmental footprint</div>	
Environmental Disclosure	Product Environmental Profile
Use Better	
<div>Materials and Substances</div>	
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Use Again	
<div>Repack and remanufacture</div>	
Circularity Profile	End of Life Information
WEEE	<div>The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins</div>
Take-back	No