



EPDU1132S

Overview

Lead time Usually in Stock	
----------------------------	--

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	3.00 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	173.8 cm
Width	5.5 cm
Output Voltage	230 V
Depth	6.2 cm
Net weight	7.9 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19

Environment

Product certifications	CE
	EAC
	ΤÜV
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	195 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	9 kg

Contractual warranty

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3169
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No