



APC Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

SRTL1000RMXLI-NC

#### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.	
Lead time	Usually in Stock	
Main		
Main Input Voltage	230 V	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	220 V 240 V	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	900 W	
Rated power in VA	1000 VA	
Input Connection Type	IEC 60320 C14	
output connection type	8 IEC 60320 C13	
Number of rack unit	3U	
Cable length	1.8 m	
Number of cables	1	
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card	

#### **Batteries & Runtime**

Range of product

Run Time	View Runtime Graph ☐
Battery type	Li-lon (Lithium-lon)
Battery voltage	48 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0

Smart-UPS On-Line

Battery recharge time	6 h
Battery life	510 year(s)
Battery charger power	103 W rated

### General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Lithium-lon
Redundant	No
UPS type	Double conversion online

# **Physical**

•	
Colour	Black with silver front bezel
Height	8.5 cm
Width	43.2 cm
Depth	56 cm
Net weight	13.7 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

## Input

Input voltage limits	160275 V 40% load 80150 V
Network frequency	4070 Hz auto-sensing

# Output

Bypass type	Built-in bypass
Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	900 W
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

### Conformance

Product certifications	CE EAC RCM VDE UK PSTI
Marking	CE Mark

12 Mar 2025

EN/IEC 62040-2:2018

#### **Environmental**

Acoustic level	50 dBA
Heat dissipation	400 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.0000000000 m
IP degree of protection	IP20
Relative humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

# **Communications & Management**

Emergency power off	Yes	
Free slots	0	
Preinstalled device	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

### **Surge Protection and Filtering**

Surge energy rate 340 J

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	60 cm
Package 1 Length	81 cm
Package 1 Weight	21 kg

### **Contractual warranty**

Warranty 5 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

#### ∅ Environmental footprint

Environmental Disclosure

Optimized Energy Efficiency

**Product Environmental Profile** 

Energy efficient product

#### **Use Better**

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
<sup>⋯</sup> Energy efficiency	

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes