

Product datasheet

Specifications



APC Easy Rack PDU, Basic, 0U, 1 Phase, 3.7kW, 230V, 16A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet

EPDU1116B

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.00 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	90.2 cm
Width	6.2 cm
Output Voltage	230 V
Depth	4.44 cm
Net weight	2.2 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CE TÜV
Ambient air temperature for operation	0...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	132 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	2.98 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	56
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Use Again	
Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No