

Product datasheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 24U, Shock Packaging, 1250 lbs, Black, 1200H x 600W x 1070D mm

AR3104SP1

Overview

Presentation NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 1250 lbs (566 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).

Lead time Usually in Stock

Main

Product or component type Rack enclosure

Number of rack unit 24U

Provided equipment

- Baying hardware
- Doors
- Installation guide
- Keyed-alike doors and side panels
- Leveling feet
- Mounting hardware
- Pallet ramps
- Pre-installed casters
- Reusable packaging
- Roof
- Side panels

Physical

Height 120 cm

Width 60 cm

Depth 107 cm

Net weight 89.09 kg

Colour Black

Mounting preference No preference

Mounting mode Not rack-mountable

Maximum mounting depth 91.49 cm

minimum mounting depth 19.1 cm

Rack width 19"

Marking

- 14 gauge EIA mounting rail
- 16 gauge front door
- 16 gauge post
- 18 gauge rear door
- 18 gauge roof
- 18 gauge side panels

Permanent permissible load

- 1020.6 kg dynamic
- 1360.8 kg static

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

| | |
|-----------|-----------------------------------|
| Standards | UL 2416 UL 60950-1 EIA-310E |
|-----------|-----------------------------------|

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

| | |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

| | |
|------------------|--------|
| Package 1 Height | 135 cm |
|------------------|--------|

| | |
|-----------------|----------|
| Package 1 Width | 121.9 cm |
|-----------------|----------|

| | |
|------------------|---------|
| Package 1 Length | 89.9 cm |
|------------------|---------|

| | |
|------------------|-----------|
| Package 1 Weight | 106.82 kg |
|------------------|-----------|

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 5 year repair or replace |
|----------|--------------------------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

| | |
|---|-----|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 324 |
|---|-----|

Use Better

Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

Yes