



APC Easy Rack PDU, Basic, 0U, 3 Phase, 11kW, 230V, 16A, 36 x C13 and 6 x C19 outlets, IEC60309 3P+N+PE inlet

EPDU1216B

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.0 m
Number of cables	1

Complementary

Input Voltage	400 V 3 phases	
Height	150.6 cm	
Width	6.2 cm	
Output Voltage	230 V	
Depth	4.44 cm	
Net weight	3.08 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Input current limits	16 A	
Load capacity	11000 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19	

Environment

Product certifications	CE TÜV
	EAC RCM
Ambient air temperature for operation	-545 °C

Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	166 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	4.28 kg

Contractual warranty

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	79
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No