

# Product datasheet

Specifications



## Rack Mount, Security and Environmental Appliance, NetBotz, 750

NBRK0750

### Overview

Presentation	The NetBotz Rack Monitor 750 provides integrated surveillance, sensing, access control, and advanced alerting for IT environments of all sizes, from single-rack edge networks to large data centers.
Lead time	Usually in Stock

### Main

Product or component type	Industrial rack PC
Range of product	Netbotz
Number of rack unit	1U
Communication port protocol	A-Link DHCP HTTPS IPv4 SNMP v1 SNMP v3 SSH v2 TCP/IP
Provided equipment	Rack mounting brackets Temperature/humidity sensor USB cable
Product compatibility	Rack sensor pod 150 Room sensor pod 155

### General

Camera frame rate	Up to 30 fps
Display resolution	Up to 1280x1024
Universal sensor supported	0-5V Door contact Dry contact Humidity Smoke Fluid spot leak Temperature Vibration
Number of universal sensor ports	6
Number of sensor pods supported	12
Number of universal sensors supported	78
Number of supported camera	4

### Physical

Colour	Black
--------	-------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	4.3 cm
Width	43.2 cm
Depth	17.8 cm
Net weight	2.45 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

## Conformance

Standards	CSA C22.2 No. 60950-1-03 FCC part 15 class A ICES-003 UL 60950-1
Product certifications	2014/30/EU AS/NZS 3548 (C-Tick) class A CE EMC directive 2004/108/EC VCCI class A

## Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Storage altitude	0.0000000000...15240.0000000000 m
Storage Relative Humidity	0...95 %

## Communications & Management

Communication network type	RJ45 10/100/1000 Base-T
----------------------------	-------------------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.500 cm
Package 1 Width	31.500 cm
Package 1 Length	53.500 cm
Package 1 Weight	4.163 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	8.976 kg

Unit Type of Package 3	P12
Number of Units in Package 3	8
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	47.904 kg

## Contractual warranty


Warranty	2 years
----------	---------

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
REACH Regulation	<a href="#">REACH Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

Use Again

 Repack and remanufacture	
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No