



APC Smart-UPS Ultra On-Line, 2200VA, Lithium-ion, Rack/Tower 1U, 230V, 3x C13, 2x C19 IEC outlets, Network Card, Extended runtime, W/rail kit

SRTL2K2RM1UINC

#### **Overview**

Lead time	Usually in Stock
Main	
Main Input Voltage	230 V AC
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	230 V
Main Output Voltage	230 V AC
Other Output Voltage	230 V
Rated power in W	2200 W
Rated power in VA	2200 VA
Input Connection Type	BS1363A British IEC 320 C19/C21 Schuko CEE 7 / EU1-16P
output connection type	3 IEC 320 C13 2 IEC 320 C19
Number of rack unit	1U
Cable length	2.4 m
Number of cables	1
Battery type	Li-lon (Lithium-lon)
Provided equipment	RJ45 cable Rack mounting brackets Network cable Terminal Stabilization feet Safety guide Rail extension Washer USB cable Screws

### **Batteries & Runtime**

Range of product

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery recharge time	1.5 h
Number of battery replacement quantity	1

Smart-UPS Ultra

Battery voltage	50 V
Battery charger power	448 W rated
Battery design life	810 year(s)
Battery life	810 year(s)
Replacement battery	APCRBC173-LI ☐
Extended runtime	1

## General

product web sub-family	High density
Redundant	No

# **Physical**

Colour	Silver grey
Height	43 mm
Width	432 mm
Depth	560 mm
Net weight	15.9 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting position	Horizontal Vertical

# Input

Network frequency	50/60 Hz auto-sensing
Input voltage limits	160275 V adjustable 220240 V AC

# Output

Maximum configurable power in W	2200 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3:1
UPS type	On-Line
Wave type	Sine wave
Output harmonic distortion	< 2% at 100% linear load and < 5% at 100% non-linear load
Bypass type	Internal bypass (automatic and manual)
Efficiency	97 %
Maximum configurable power in VA	2200 VA

### Conformance

Product certifications	CE EAC RCM VDE UKCA UK PSTI
Marking	CE Mark
Standards	EN/IEC 62040-1 FCC CFR 47 part 15 class A IEC 62040-2 EN/IEC 61000-4-8 EN/IEC 61000-4-6 level 3 EN/IEC 61000-4-5 level 3 EN/IEC 61000-4-4 level 4

### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	0.000000000015240.000000000 m
Acoustic level	55 dB
Heat dissipation	325 Btu/h
IP degree of protection	IP20

## **Communications & Management**

Preinstalled device	Network management card with environmental monitoring
control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use USB: port monitoring RJ45: port monitoring feature availability varies by terms of use

## **Surge Protection and Filtering**

Surge energy rate	1600 J

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.82 cm
Package 1 Width	56.4 cm
Package 1 Length	76.4 cm
Package 1 Weight	24.18 kg

# **Contractual warranty**

Warranty	5 years repair or replace	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	5818
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances		
EU RoHS Directive	Compliant with Exemptions	
REACh Regulation	REACh Declaration	
China RoHS Regulation	China RoHS declaration	

#### **Use Again**

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Removable battery	User replaceable	
Take-back	No	