

Product datasheet

Specifications



APC Smart-UPS On-Line,
1500VA, Lithium-ion, Rackmount
4U, 230V, 8x C13 IEC outlets,
Network Card, Extended long
runtime, Rail kit included

SRTL1500RM4UXLI-NC

Overview

Presentation	High density, double-conversion on-line power protection with long runtime with NMC
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	1350 W
Rated power in VA	1500 VA
Input Connection Type	IEC 60320 C14
output connection type	8 IEC 60320 C13
Number of rack unit	4U
Cable length	1.8 m
Number of cables	1
Range of product	Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph
Battery type	Li-Ion (Lithium-Ion)
Battery voltage	48 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery life	5...10 year(s)
Battery charger power	103 W rated

General

Number of power module filled slots	0
Number of power module free slots	0

product web sub-family	Lithium-Ion
Redundant	No
UPS type	Double conversion online

Physical

Colour	Black with silver front bezel
Height	8.5 cm
Width	43.2 cm
Depth	56 cm
Net weight	13.7 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Input voltage limits	160...275 V
Network frequency	40...70 Hz auto-sensing

Output

Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	1350 W
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CE UK PSTI
Marking	CE Mark

Environmental

Acoustic level	50 dBA
Heat dissipation	450 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
IP degree of protection	IP20

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Communications & Management

Emergency power off	Yes
---------------------	-----

Free slots	0
------------	---

Preinstalled device	Network management card 3 with environmental monitoring
---------------------	---

Alarm	Audible and visible alarms : prioritized by severity
-------	--

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	24.5 cm
------------------	---------

Package 1 Width	60 cm
-----------------	-------

Package 1 Length	81 cm
------------------	-------

Package 1 Weight	21 kg
------------------	-------

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Energy efficiency

Product contributes to saved and avoided emissions

Yes

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No