

# Product datasheet

Specifications



APC Smart-UPS C, Line Interactive, 1000VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

SMC1000I-2UC

## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
--------------	---

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	600 W
Rated power in VA	1000 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 320 C14
Output connection type	4 IEC 320 C13 2 IEC Jumpers
Number of rack unit	2U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Documentation CD Installation guide Rack mounting brackets USB cable
Range of product	Smart-UPS

## Complementary

Communication port type	SmartConnect Ethernet port
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
----------	------------------------------------

Efficiency	<a href="#">View Efficiency Graph</a>
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	4...6 year(s)
Replacement battery	<a href="#">APCRBC124</a>
Battery charger power	72 W rated

## General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Colour	Black
Height	8.6 cm
Width	43.2 cm
Depth	40.6 cm
Net weight	20.52 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	1
USB compatible	Yes

## Input

Input voltage limits	170...300 V adjustable 180...287 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	600 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave

<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
-------------------------	---------------------------------

## Conformance

<b>Product certifications</b>	C-Tick CE GOST VDE UK PSTI
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Acoustic level</b>	42 dBA
<b>Heat dissipation</b>	46 Btu/h
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0.000000000...15240.000000000 m
<b>Relative humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Communications & Management

<b>control panel</b>	Multifunction LCD status and control console
<b>Free slots</b>	0
<b>Communication port support</b>	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

<b>Surge energy rate</b>	459 J
<b>Noise suppression</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	24.1 cm
<b>Package 1 Width</b>	58.4 cm
<b>Package 1 Length</b>	54.6 cm
<b>Package 1 Weight</b>	22.33 kg

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **946**

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

#### Energy efficiency

Optimized Energy Efficiency Energy efficient product

### Use Again

#### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery User replaceable

Take-back Yes