Specifications



Power Cord, C19 to IEC309 16A, 2.5m

AP9876

Overview

Lead time

Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60309 16 A
Cable length	2.5 m
Number of cables	1

Physical

Colour	Black
Net weight	0.24 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50/60 Hz
Permissible voltage	90250 V
Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Protection type	Without circuit breaker

Conformance

Product certifications

VDE

Environmental

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C

Storage Relative Humidity	095 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	10.2 cm
Package 1 Length	20.3 cm
Package 1 Weight	0.299 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	23.3 cm
Package 2 Width	32.5 cm
Package 2 Length	53 cm
Package 2 Weight	5.1 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	10
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	5.1 kg

Contractual warranty

Warranty

2 years repair or replace

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >				
How we assess product sustainability \geq				
∅ Environmental footprint				
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	76			
Environmental Disclosure	Product Environmental Profile			
Use Better				
ℬ Materials and Substances				
EU RoHS Directive	Compliant			
REACh Regulation	REACh Declaration			
Use Again				
$^{\circlearrowright}$ Repack and remanufacture				
Circularity Profile	End of Life Information			
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins			
Halogen content performance	Product contains halogen above thresholds			
Take-back	Yes			