



EPDU1232S

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched

Complementary

Input Voltage	400 V 3 phases	
Height	1794 mm	
Width	55 mm	
Output Voltage	230 V	
Depth	62 mm	
Net weight	8.17 kg	
Mounting location	Side	
Input Plug Type	IEC 60309 32 A 3P + N + PE	
Mounting position	Vertical	
Input current limits	32 A	
Load capacity	22 kW	
Network frequency	50/60 Hz	
Plug standard	IEC 60309	
Outlet type and quantity	18 IEC 60320 C13 6 IEC 60320 C19	

Environment

Product certifications	CE EAC RCM TÜV
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	03000 m
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1950 mm
Package 1 Width	160 mm
Package 1 Length	110 mm
Package 1 Weight	9.45 kg

Contractual warranty

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3278
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No