



Easy Rack PDU, Switched Metered Outlet, 0U, 1 Phase, 3.7kW, 230V, 16A, (20) C13 and (4) C19 outlets, IEC60309 2P+E inlet

EPDU2116SMBO

Overview

Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered outlet
Cord length	3 m
Number of cables	1
Provided equipment	Installation guide

Complementary

200 V	
1800 mm	
55 mm	
230 V	
56 mm	
6.67 kg	
Side	
No preference	
IEC 60309 16 A 2P + E	
Not rack-mountable	
0U	
No	
Vertical	
SNMP	
16 A	
200240 V	
16 A	
16 A	
3680 VA	
50/60 Hz	

Plug standard	IEC 60309
Outlet type and quantity	20 IEC 60320 C13
Communication network type	10/100BASE-T

Environment

Product certifications	CE
Ambient air temperature for operation	-550 °C
Relative humidity	595 %
Operating altitude	03000 m
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015000 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203 cm
Package 1 Width	19.5 cm
Package 1 Length	13 cm
Package 1 Weight	7.84 kg

Contractual warranty

Warranty 2 Years repair and Replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

a	Environmental footprint	
4	Environmental tootbrint	

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

Use Again

\mathcal{O}	Repack	and	remanufacture
---------------	--------	-----	---------------

Circularity Profile End of Life Information

Take-back No