



APC Replacement Battery Cartridge, Valve regulated lead– acid battery, 7Ah, 12VDC, 2-year warranty

RBC2

Overview

Lead time Usually in Stock

Main

Product or component type	Replacement battery cartridge	
Number of cables	1	
Battery type	Lead-acid battery	
Provided equipment	All required connectors Battery recycling guide Reusable packaging Installation guide	

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Battery voltage	12 V
Number of battery replacement quantity	1

Physical

Colour	Black
Height	9.4 cm
Width	6.4 cm
Depth	15.1 cm
Net weight	2.5 kg
Mounting mode	Not rack-mountable
USB compatible	No

Output

Battery capacity 7.0 Ah

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	010000 ft
Relative humidity	095 %
Ambient air temperature for storage	-1545 °C

Storage altitude	0.000000000015240.0000000000 m
Storage Relative Humidity	0. 95 %

Packing Units

PCE
1
8.900 cm
17.500 cm
21.300 cm
2.769 kg
S02
2
15.000 cm
30.000 cm
40.000 cm
5.540 kg
P12
32
30.000 cm
80.000 cm
120.000 cm
100.000 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	9
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes