



Easy Rack PDU, Switched Metered Outlet, 0U, 1 Phase, 7.4kW, 230V, 32A, (20) C13 and (4) C19 outlets, IEC60309 2P+E inlet

EPDU2132SMBO

Overview

Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered outlet
Cord length	3 m
Number of cables	1
Provided equipment	Installation guide

Complementary

Complementary		
Input Voltage	200 V	
Height	1800 mm	
Width	55 mm	
Output Voltage	230 V	
Depth	56 mm	
Net weight	7.42 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 2P + E	
Mounting mode	Not rack-mountable	
Rack units	0U	
USB compatible	No	
Mounting position	Vertical	
Communication port protocol	SNMP	
[In] rated current	32 A	
Permissible voltage	200240 V	
Max line current	32 A	
Input current limits	32 A	
Load capacity	7360 VA	
Network frequency	50/60 Hz	

Plug standard	IEC 60309	
Outlet type and quantity	20 IEC 60320 C13	
Communication network type	10/100BASF-T	

Environment

Product certifications	CE
Ambient air temperature for operation	-550 °C
Relative humidity	595 %
Operating altitude	03000 m
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203 cm
Package 1 Width	19.5 cm
Package 1 Length	13 cm
Package 1 Weight	8.59 kg

Contractual warranty

Warranty 2 Years repair and Replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

0	Environmental footprint	
Y)	Environmental tootbrint	

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

Use Again

\mathcal{O}	Repack	and	remanufacture
---------------	--------	-----	---------------

Circularity Profile End of Life Information

Take-back No