Specifications

ΔΡC



## APC NetShelter SX, Server Rack Enclosure, 42U, without Sides, Black, 2258H x 750W x 1070D mm

AR3150X609

### Overview Presentation

Presentation	Wide enclosure with increased cable management options for high density server and networking applications. 42U height to easily roll through doorways.	
Lead time	Usually in Stock	
Main		
Product or component type	Rack enclosure	
Number of rack unit	42U	
Provided equipment	Baying hardware Casters Door key Doors Leveling feet	

Rack mounting hardware

Roof

### **Physical**

•		
Height	199.14 cm	
Width	75 cm	
Depth	107 cm	
Net weight	126.86 kg	
Colour	Black	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Mounting location	Front	
Maximum mounting depth	91.49 cm	
minimum mounting depth	26.19 cm	
Rack width	19"	
Marking	14 gauge EIA mounting rail	
	16 gauge front door	
	16 gauge post	
	16 gauge rear door	
	18 gauge roof	
Permanent permissible load	1020.6 kg dynamic	
	1360.8 kg static	

### Conformance

#### Standards

UL 2416 UL 60950-1 EIA-310E

## **Packing Units**

<b>U</b>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	221.6 cm
Package 1 Width	121.9 cm
Package 1 Length	89.5 cm
Package 1 Weight	139.09 kg

## **Contractual warranty**

Warranty

5 year repair or replace

2

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability  $\geq$ 

#### **Use Better**

Intervals and Substances		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
REACh Regulation	REACh Declaration	
Use Again		
$^{igcelowheadrightarrow}$ Repack and remanufacture		
Circularity Profile	End of Life Information	

Take-back

Yes