



Easy Rack PDU, Switched Metered Outlet, 0U, 3 Phase, 11kW, 230V, 16A, (18) C13 and (6) C19 outlets, IEC60309 3P+N+PE inlet

EPDU2216SMBO

Overview

Lead time Usually in Stock

Main

Colour	Black	
Product or component type	nent type PDU	
PDU type	Metered outlet	
Cord length	3 m	
Number of cables	1	
Provided equipment	Installation guide	

Complementary

Input Voltage	400 V 3 phases	
Height	1800 mm	
Width	55 mm	
Output Voltage	230 V	
Depth	56 mm	
Net weight	7.12 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 3P + N + PE	
Mounting mode	Not rack-mountable	
Rack units	OU	
USB compatible	tible No	
Mounting position	Vertical	
Communication port protocol	SNMP	
[In] rated current	16 A	
Max line current	16 A	
Input current limits	16 A	
Load capacity	11000 VA	
Network frequency	50/60 Hz	
Plug standard	IEC 60309	

Outlet type and quantity	18 IEC 60320 C13 10 A
Communication network type	10/100BASE-T

Environment

Product certifications	CE
Ambient air temperature for operation	-550 °C
Relative humidity	595 %
Operating altitude	03000 m
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203 cm
Package 1 Width	19.5 cm
Package 1 Length	13 cm
Package 1 Weight	8.29 kg

Contractual warranty

Warranty 2 Years repair and Replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

0	Environmental footprint	
Y)	Environmental tootbrint	

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

Use Again

\mathcal{O}	Repack	and	remanufacture
---------------	--------	-----	---------------

Circularity Profile End of Life Information

Take-back No