

Product datasheet

Specifications



InRow RD, 300mm, Fluid Cooled, 220-240V, 50Hz

ACRD201

Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

Main

Main Input Voltage	220 V 240 V
Number of rack unit	42U
Provided equipment	Installation guide Operations and maintenance manual

General

Compressor type	Scroll
Air discharge option	Horizontal
Intake air option	Rear return
air flow	1080.8 l/s
Condensate pump flow	0.010 m3/h

Physical

Colour	Black
Height	199.1 cm
Width	30 cm
Depth	107 cm
Net weight	199.09 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Input power	4400 W
Network frequency	50 Hz

Conformance

Product certifications	cUL listed C-Tick CE UL listed
------------------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Communications & Management

control panel	Multifunction LCD status and control console
---------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	211.8 cm
Package 1 Width	113.7 cm
Package 1 Length	74.6 cm
Package 1 Weight	241.82 kg

Contractual warranty

Warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up
----------	--



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Use Again

Repack and remanufacture	
Take-back	No