


Product datasheet

Specifications



InRow RC, 600mm, Chilled Water, 380-415V, 50/60Hz

ACRC602

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
Input Connection Type	IEC 60309 16 A 3P + N + PE
Number of rack unit	42U
Number of cables	2
Provided equipment	Installation guide Operations and maintenance manual

General

Air discharge option	Horizontal
Intake air option	Rear return
air flow	2831.7 l/s
Minimum water inlet temperature	45 °F
Condensate pump flow	0.03 m3/h

Physical

Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net weight	345.45 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Conformance

Product certifications	cUL listed CE Industry Canada UL listed VDE
------------------------	---

Communications & Management

control panel Multifunction LCD status and control console

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	216.6 cm
Package 1 Width	113.7 cm
Package 1 Length	85 cm
Package 1 Weight	405.45 kg
Number of Units in Package 3	1

Contractual warranty

Warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up
----------	--

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

Take-back

No