



APC Replacement Battery Cartridge for Smart-UPS Line Interactive, 120V 5Ah lead-acid battery, 2- year repair or replace warranty

APCRBC117

## Overview

Lead time Usually in Stock

## Main

Product or component type	Replacement battery cartridge	
Battery type	Lead-acid battery	
Provided equipment	All required connectors Battery recycling guide Installation guide Reusable packaging	
Range of product	Replacement Battery Cartridges	

## **Batteries & Runtime**

Number of battery blocks per string	10	
Number of battery free slots	0	
Number of battery filled slots	0	
Device mounting	Enclosed battery cartridge	
Battery voltage	120 V	
Number of battery replacement quantity	1	

## **Physical**

Height	7.6 cm
Width	20.3 cm
Depth	58.4 cm
Net weight	22.27 kg
Mounting mode	Not rack-mountable

## **Environmental**

Ambient air temperature for operation	040 °C
Operating altitude	010000 ft
Relative humidity	095 %
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.000000000 m

Storage Relative Humidity 0...95 %

# **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.8 cm
Package 1 Width	39.3 cm
Package 1 Length	76.1 cm
Package 1 Weight	25.18 kg
SCC14	731304282679

## **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	82
Environmental Disclosure	Product Environmental Profile

## **Use Better**

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes