



InRow RD, 600mm Air Cooled, 380-415V, 50/60Hz

ACRD602

Overview

Lead time Special Order - Call for Quoted Lead Times

Main	
Main Input Voltage	380 V 3 phases 400 V 3 phases 415 V 3 phases
Number of rack unit	42U
Provided equipment	Door key Installation guide Integrated network management Network management card Operations and maintenance manual User manual

General

Compressor type	Scroll
Air discharge option	Horizontal
Intake air option	Rear return
air flow	1887.8 l/s
Inrush current	28 A
Condensate pump flow	0.1 m3/h
Tube material	Copper

Physical

Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net weight	391 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Number of feeders	1	
Input power	14600 W	
Network frequency	50/60 Hz	

Number of input connectors 1 hard wire 4-wire (3P + E)

Conformance

Product certifications

C-Tick

CE

EAC

Environmental

Ambient air temperature for operation	-2050 °C
Relative humidity	595 %
Operating altitude	010000 ft
Acoustic level	84 dBA

Communications & Management

control panel Multifunction LCD status and control console

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	216.6 cm
Package 1 Width	113.7 cm
Package 1 Length	85 cm
Package 1 Weight	436 kg
Number of Units in Package 3	1

Contractual warranty

Warranty

1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
. L. Con regulation	<u></u>
Use Again	
○ Repack and remanufacture	
Take-back	No