



APC Smart-UPS, Line Interactive, 3kVA, Rackmount 2U, 230V, 8x IEC C13+1x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT3000RMI2UC

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock
Main	
Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	BS1363A British IEC 320 C20 Schuko CEE 7 / EU1-16P
output connection type	8 IEC 320 C13 3 IEC Jumpers 1 IEC 320 C19
Number of rack unit	2U
Cable length	2.00 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Documentation CD Rack mounting hardware Rack mounting support rails USB cable

Complementary

Range of product

Communication port type	SmartConnect Ethernet port SmartSlot
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

Smart-UPS

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	RBC43 ☐
Battery charger power	182 W rated

General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

Physical

Height	8.6 cm
Width	43.2 cm
Depth	68.3 cm
Net weight	44.28 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Input voltage limits	151302 V adjustable 160286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Transfer time	6 ms typical : 10 ms maximum

UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CE	
	EAC	
	IRAM	
	RCM	
	VDE	
	UK PSTI	
Marking	GS Mark	
Standards	EN/IEC 62040-1:2019/A11:2021	
	EN/IEC 62040-2:2006/AC:2006	
	EN/IEC 62040-2:2018	

Environmental

Acoustic level	55 dBA
Heat dissipation	348 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

control panel	Multifunction LCD status and control console
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate 320 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	98.044 cm
Package 1 Width	59.995 cm
Package 1 Length	25.400 cm
Package 1 Weight	51.592 kg

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2969
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
[™] Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes