

Specifications

APC



APC Replacement Battery Cartridge for Smart-UPS Line Interactive, 12V 17Ah lead-acid battery, 2-year repair or replace warranty

RBC55

Overview		
Lead time	Usually in Stock	
Main		
Product or component type	Replacement battery cartridge	
Number of cables	1	
Battery type	Lead-acid battery	
Provided equipment	All required connectors Battery recycling guide Reusable packaging Installation guide	
Range of product	Replacement Battery Cartridges	

## **Batteries & Runtime**

Number of battery free slots	0
Number of battery filled slots	0
Number of battery replacement quantity	2

## Physical

•		
Colour	Black	
Height	17.3 cm	
Width	14.2 cm	
Depth	18.3 cm	
Net weight	24.27 kg	
Mounting mode	Not rack-mountable	
USB compatible	No	

## Environmental

Ambient air temperature for operation	040 °C	
Operating altitude	010000 ft	
Relative humidity	095 %	
Ambient air temperature for storage	-1545 °C	
Storage altitude	0.00000000015240.000000000 m	

Storage Relative Humidity 0...95 %

#### **Packing Units**

V	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.7 cm
Package 1 Width	29.5 cm
Package 1 Length	53.8 cm
Package 1 Weight	26.68 kg

# **Contractual warranty**

Warranty

2 years repair or replace

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

# Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 87

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
REACh Regulation	REACh Declaration	
China RoHS Regulation	China RoHS declaration	
Use Again		

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	Yes	