



APC Replacement Battery Cartridge for Smart-UPS Line Interactive, 48V 9Ah lead-acid battery, 2-year repair or replace warranty

APCRBC115

Overview

Lead time Usually in Stock

Main

Product or component type	Replacement battery cartridge	
Battery type	Lead-acid battery	
Provided equipment	All required connectors Battery recycling guide Installation guide Reusable packaging	
Range of product	Replacement Battery Cartridges	

Batteries & Runtime

Battery location	Internal battery
Number of battery blocks per string	4
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Enclosed battery cartridge
Battery voltage	48 V
Number of battery replacement quantity	1

Physical

Colour	Black
Height	8.3 cm
Width	16.5 cm
Depth	41.9 cm
Net weight	10.82 kg
Mounting mode	Not rack-mountable

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	010000 ft
Relative humidity	095 %

Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.0000000000 m
Storage Relative Humidity	0. 95 %

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19 cm
Package 1 Width	29.2 cm
Package 1 Length	54.6 cm
Package 1 Weight	11.73 kg
SCC14	731304281689

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	38
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes