



APC Netshelter Rack Automatic Transfer Switch, 2U, 30A, 200/208V, 2 L6-30 IN, 16 C13, 2 C19 OUT, 50/60Hz

AP4432A

Overview

Lead time	Usually in Stock	

Main

Main Input Voltage	200 V AC 1 phase 208 V	
Product or component type	Automatic transfer switch	
Main Output Voltage	200 V AC 1 phase 208 V	
Input Connection Type	NEMA L6-30P 24 A 2P + E	
Number of rack unit	2U	
Cable length	2.4 m	
Number of cables	2	
Provided equipment	Mounting hardware Rack mounting brackets	

Physical

Colour	Black	
Height	8.8 cm	
Width	43.2 cm	
Depth	23.6 cm	
Net weight	6.58 kg	
Mounting location	Front Rear	
Mounting preference	No preference	
Mounting mode	Rack-mounted	
Mounting position	Horizontal	

Input

Network frequency	50/60 Hz
[In] rated current	30 A
Permissible voltage	180220 V
Max line current	30 A
Input current limits	30 A
Load capacity	4992 VA

Output

Max current draw	30 A	
Number of power socket outlets	16 IEC 60320 C13 12 A 2P + E 2 IEC 60320 C19 16 A 2P + E	
Protection type	Circuit breaker	
Power cable length	2.44 m	

Conformance

Product certifications	PSE TÜV-C TÜV-NURTL
Standards	EN 55022 class A FCC part 15 class A

Environmental

Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21 cm
Package 1 Width	58.4 cm
Package 1 Length	35.6 cm
Package 1 Weight	9.07 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

12 Mar 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	755
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes