

Product datasheet

Specifications

APC



APC Symmetra LX 8kVA Scalable to 8kVA N+1 Rack-mount, 220/230/240V or 380/400/415V

SYA8K8RMI

Overview

Presentation	High performance, redundant power protection with scalable power and runtime for space-constrained server rooms, and voice and data networks.
---------------------	---

Lead time	Usually in Stock
------------------	------------------

Main

Main Input Voltage	230 V 400 V 3 phases
---------------------------	-------------------------

Product or component type	Uninterruptible power supply (UPS)
----------------------------------	------------------------------------

Other Input Voltage	220 V 240 V 380 V 415 V
----------------------------	----------------------------------

Main Output Voltage	230 V
----------------------------	-------

Other Output Voltage	220 V 240 V
-----------------------------	----------------

Rated power in W	5600 W
-------------------------	--------

Rated power in VA	8000 VA
--------------------------	---------

Output connection type	8 IEC 60320 C13 6 IEC 60320 C19
-------------------------------	------------------------------------

Output connector type	Hard wire 3-wire (H N + E) 1
------------------------------	------------------------------

Number of rack unit	13U
----------------------------	-----

Battery type	Lead-acid battery
---------------------	-------------------

Provided equipment	CD with software Documentation CD Installation guide User manual Web/SNMP management card
---------------------------	---

Range of product	Symmetra LX
-------------------------	-------------

Batteries & Runtime

Run Time	View Runtime Graph
-----------------	------------------------------------

Number of battery filled slots	2
---------------------------------------	---

Number of battery free slots	0
-------------------------------------	---

Battery recharge time	3 h
------------------------------	-----

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
-------------------------------	--

Battery charger power	574 W rated
------------------------------	-------------

Battery life	3...5 year(s)
---------------------	---------------

Extended runtime	1
------------------	---

General

product web sub-family	4kVA power increments
Number of power module free slots	1
Number of power module filled slots	2
Redundant	Yes

Physical

Colour	Black Silver
Height	57.2 cm
Width	47.2 cm
Depth	68.8 cm
Net weight	178.18 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Network frequency	45...65 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Input voltage limits	155...276 V 290...480 V 3:1
Input harmonic distortion	Less than 7 % for full load
Input Power Factor at Full Load	0.98

Output

Maximum configurable power in W	5600 W
Harmonic distortion	Less than 5 % at full load
Output frequency	47...63 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	Up to 5 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Efficiency	90 % (full load)
Maximum output current	36 A
Maximum configurable power in VA	8000 VA

Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN 50091-1 EN 50091-2 EN 55022 class A EN 55024 EN 60950 IEC 60950

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...4572.0000000000 m
Acoustic level	62 dBA
Heat dissipation	2762 Btu/h

Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring
control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.7 cm
Package 1 Width	59.9 cm
Package 1 Length	99.7 cm
Package 1 Weight	216.82 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **30526**

Use Better

Materials and Substances

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Removable battery User replaceable

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back Yes