

Product datasheet

Specifications



APC SYMMETRA LX 3 BATTERY RACK-MOUNT XR FRAME, 230V

SYBFXR3RMI

Overview

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

Main

Product or component type	Battery accessory
Number of rack unit	5U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Installation guide User manual
Range of product	Symmetra Battery Systems

Batteries & Runtime

Battery location	Battery cabinet
Number of battery free slots	3
Number of battery filled slots	0
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cabinet
Number of battery replacement quantity	3

Physical

Colour	Black
Height	21.5 cm
Width	47.2 cm
Depth	68.6 cm
Net weight	26.82 kg
Mounting mode	Rack-mounted

Conformance

Standards	EN 50091-1 EN 50091-2 EN 60950 IEC 60950
-----------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	BSMI VCCI VDE
------------------------	---------------------

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...4572.0000000000 m
Storage Relative Humidity	0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.3 cm
Package 1 Width	98 cm
Package 1 Length	59.9 cm
Package 1 Weight	30.92 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	94

Use Better	
Materials and Substances	
[EU RoHS Directive](#)	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	[REACH Declaration](#)
Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
Use Again	
Repack and remanufacture	
Circularity Profile	[End of Life Information](#)
Removable battery	User replaceable
Take-back	Yes