# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# APC Symmetra LX Extended Run Rack-mount w/ 3 SYBT5, 230V

SYARMXR3B3I

### Overview

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

### Main

Product or component type	Battery accessory
Number of rack unit	5U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Installation guide User manual
Range of product	Symmetra Battery Systems

### **Batteries & Runtime**

Battery location	Battery cabinet	
Number of battery free slots	0	
Number of battery filled slots	0	
Battery manufacturer	Panasonic	
Device mounting	Enclosed battery cabinet	
Number of battery replacement quantity	3	

### **Physical**

Colour	Black
Height	21.5 cm
Width	47.2 cm
Depth	68.6 cm
Net weight	114.1 kg
Mounting mode	Rack-mounted

### Conformance

Standards	EN 50091-1	
	EN 50091-2	
	EN 60950	
	IEC 60950	

Product certifications	BSMI	
i roddot oortinoddono	DOMI	
	VCCI	
	V 001	
	VDE	

### **Environmental**

Ambient air temperature for operation	040 °C	
Operating altitude	010000 ft	
Relative humidity	095 %	
Ambient air temperature for storage	-1545 °C	
Storage altitude	0.00000000004572.000000000 m	
Storage Relative Humidity	095 %	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.3 cm
Package 1 Width	98 cm
Package 1 Length	59.9 cm
Package 1 Weight	127.74 kg

## **Contractual warranty**



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

Removable battery

Take-back

How we assess product sustainability >

### **Use Better**

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
REACh Regulation	REACh Declaration	
<sup>™</sup> Energy efficiency		
Optimized Energy Efficiency	Energy efficient product	
Use Again		
○ Repack and remanufacture		

User replaceable