



# APC Replacement Battery Cartridge 142 with 2 Year Warranty

APCRBC142

## **Overview**

Lead time Usually in Stock

### Main

Product or component type	Replacement battery cartridge	
Battery type	Lead-acid battery	
Provided equipment	All required connectors	
	Battery recycling guide	
	Installation guide	
	Reusable packaging	
Range of product	Replacement Battery Cartridges	

### **Batteries & Runtime**

Number of battery blocks per string	2
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	24 V

# **Physical**

Height	10.8 cm
Width	13.2 cm
Depth	15 cm
Net weight	6.01 kg
Mounting mode	Not rack-mountable
USB compatible	No

## **Environmental**

Ambient air temperature for operation	040 °C
Operating altitude	010000 ft
Relative humidity	095 %
Ambient air temperature for storage	-1545 °C
Storage altitude	0.00000000015240.000000000 m

Storage Relative Humidity 0...95 %

# **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.3 cm
Package 1 Width	22.4 cm
Package 1 Length	16.8 cm
Package 1 Weight	7.01 kg
SCC14	10731304291975

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	23
Environmental Disclosure	Product Environmental Profile

### **Use Better**

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes