

Product datasheet

Specifications



17" Rack LCD Console with Integrated 8 Port Analog KVM Switch

AP5808

Overview

Presentation	The Rack LCD Console with Integrated KVM Switch combines the functionality of Rack LCD Console and Analog KVM switches in one convenient package optimizing U space in the rack environment, eliminating cable clutter, and offering a value of two products functionality in one package. Keyboard is a US English keyboard layout.
--------------	--

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V 240 V
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Cable length	1.8 m
Number of cables	1
Provided equipment	USB KVM cable Single user rack mount kit PS2 KVM cable NEMA 5-15 power cord Installation guide Firmware upgrade cable Documentation CD C13-C14 power cord

Physical

Colour	Black
Height	4.3 cm
Width	48.3 cm
Depth	71.1 cm
Net weight	13.77 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Maximum mounting depth	104.98 cm
minimum mounting depth	68 cm

Input

Network frequency	50/60 Hz
-------------------	----------

Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	cUL listed C-Tick CE Industry Canada KCC UL listed VDE TAA compliance
Standards	EN 60950 FCC part 15 class A IEC 60950

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Supported Hardware

Display colour	16 colours
Display size	337.9 (H) x 270.3 (V) 17 inch
Trackball type	PS/2 touchpad USB mouse
Display type	LCD display

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13 cm
Package 1 Width	83 cm
Package 1 Length	66.5 cm
Package 1 Weight	19.86 kg





Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

<div>Environmental footprint</div>	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	60
Use Better	
<div>Materials and Substances</div>	
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
Use Again	
<div>Repack and remanufacture</div>	
Circularity Profile	End of Life Information
WEEE	<div>The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins</div>
Take-back	Yes