

# Product datasheet

Specifications



## Symmetra PX40KW Extended Run Battery Frame with Startup

SYCFXR8S

### Overview

Lead time Usually in Stock

### Main

Number of cables	1
Battery type	VRLA
Provided equipment	Installation guide Start-up service User manual

### Batteries & Runtime

Number of battery free slots	8
Number of battery filled slots	0
Battery life	3...5 year(s)
Device mounting	Enclosed battery cabinet

### Physical

Colour	Black
Height	207 cm
Width	58.4 cm
Depth	90.2 cm
Net weight	250 kg

### Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...3333 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	208.3 cm

---

Package 1 Width	101.6 cm
Package 1 Length	76.2 cm
Package 1 Weight	272.73 kg

---

## Contractual warranty

---

Warranty	1 year repair or replace
----------	--------------------------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO<sub>2</sub> per CR, Total Life cycle) **1**

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

### Use Again

#### Repack and remanufacture

Removable battery User replaceable

Take-back Yes