

Product datasheet

Specifications



RACK PDU, BASIC, VERTICAL, 220-240V, 32A, (20) C13, (6) C19

AP6009A

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	PDU
PDU type	Basic
Cord length	3.05 m
Number of cables	1
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	230 V
Height	162.6 cm
Width	5.6 cm
Output Voltage	230 V
Depth	4.3 cm
Net weight	6.18 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Not rack-mountable
Rack units	0U
Mounting position	Vertical
Permissible voltage	200...240 V
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13 6 IEC 60320 C19

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CE EAC IRAM VDE
Ambient air temperature for operation	0...50 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	187.5 cm
Package 1 Width	13.5 cm
Package 1 Length	22.6 cm
Package 1 Weight	8 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	156
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Product contains halogen above thresholds
Take-back	Yes