



APC Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 208V-230V, 8x C13+1x C19 IEC, Network card, Extended runtime

SMX2200R2HVNC

#### **Overview**

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock
Main	
Main Input Voltage	208 V 230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	208 V 230 V
Other Output Voltage	220 V 240 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	BS1363A British IEC 320 C20 Schuko CEE 7 / EU1-16P
output connection type	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Number of rack unit	2U
Cable length	1.8 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Installation guide Network management card Rack mounting support rails Smart UPS signalling RS-232 cable Temperature probe USB cable
Range of product	Smart-UPS

#### **Batteries & Runtime**

Run Time View Runtime Graph ☐

Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC117 ☐
Battery charger power	233 W rated

### General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Extended run
Redundant	No

## **Physical**

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	66.7 cm
Net weight	37.24 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	140280 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

# Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

### Conformance

Product certifications	CE EAC IRAM RCM TISI VDE
	UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

### **Environmental**

Acoustic level	55 dBA
Heat dissipation	150 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.0000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

## **Communications & Management**

control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators Multifunction LCD status and control console
Emergency power off	Yes
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## **Surge Protection and Filtering**

Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.300 cm
Package 1 Width	86.900 cm
Package 1 Length	59.600 cm
Package 1 Weight	45.260 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	2
Package 2 Height	90.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm

Package 2 Weight	103.522 kg
Pallet unit layers	2
Pallet lavers	4

## **Contractual warranty**

Warranty

3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3167
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
<sup>™</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes