
Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications







AP6031A

Overview

Lead time Usually in Stock

Main

Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Cord length	3.7 m	
Provided equipment	Installation guide Safety guide	

Complementary

Complementary		
200 V		
208 V		
4.4 cm		
43.8 cm		
200 V		
208 V		
12.6 cm		
3.8 kg		
Front		
Rear		
No preference		
NEMA L6-30P		
Not rack-mountable		
1U		
No		
Horizontal		
24 A		
30 A		
30 A		
5000 VA		
50/60 Hz		
4 IEC 60320 C19		

Environment

Product certifications	cUL listed
	UL listed

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.1 cm
Package 1 Width	18 cm
Package 1 Length	47.3 cm
Package 1 Weight	4.6 kg
SCC14	10731304327810

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	94		
Environmental Disclosure	Product Environmental Profile		

Use Better

EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	
Optimized Energy Efficiency	Energy efficient product	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Product contains halogen above thresholds
Take-back	Yes