Product datasheet

Specifications



Symmetra PX 40KW Extended Run Battery Frame with 8 Battery Modules & Startup

SYCFXR8-8

Overview

Lead time

Usually in Stock

Main

Main Input Voltage	208 V 3 phases
Number of cables	1
Battery type	VRLA
Provided equipment	Installation guide Start-up service User manual

Batteries & Runtime

Battery location	Battery cabinet
Number of battery blocks per string	32
Number of battery free slots	0
Number of battery filled slots	8
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cabinet
Battery voltage	192 V

Physical

Colour	Black
Height	207 cm
Width	58.4 cm
Depth	90.2 cm
Net weight	985 kg

Input

Network frequency	50/60 Hz +/- 5 Hz auto sensing
Number of input connectors	1 hard wire 4-wire (3P + E)

Conformance

Product certifications

EUROBAT

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	03333 ft
Relative humidity	095 %
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	231.1 cm
Package 1 Width	101.6 cm
Package 1 Length	76.2 cm
Package 1 Weight	1000 kg

Contractual warranty

Warranty

1 year repair or replace

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >	
How we assess product sustainability \geq	
${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
Materials and Substances EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
EU RoHS Directive	scope)
EU RoHS Directive REACh Regulation	scope)
EU RoHS Directive REACh Regulation Use Again	scope)