

Product datasheet

Specifications



APC Easy UPS 1 Ph Line
Interactive, 1500VA, Tower, 230V,
6 IEC C13 outlets, AVR, Dry
Contact, LCD, Without Network
Card support

SMV1500CAI

Overview

Presentation	Easy UPS provides power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Input voltage	220 V 240 V
Main Output Voltage	230 V
Rated power in W	1050 W
Rated power in VA	1500 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	6 IEC 60320 C13
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Documentation CD User manual USB cable
Range of product	Easy UPS

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery voltage	24 V
Battery charger power	54 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBCV207
Extended runtime	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Colour	Black
Height	22 cm
Width	16 cm
Depth	41 cm
Net weight	17.8 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	45...65 Hz +/- 1 Hz auto-sensing
Input voltage limits	165...290 V

Output

Maximum configurable power in W	1050 W
Output frequency	50/60 Hz +/- 1 Hz unsynchronised
Crest factor	3 : 1
UPS type	Line interactive
Wave type	Sine wave
Graph display	1
Maximum configurable power in VA	1500 VA
Transfer time	2-6 ms typical : 12 ms maximum

Conformance

Product certifications	CE UKCA EAC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m

Ambient air temperature for storage	-10...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	45 dBA
IP degree of protection	IP20

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	190 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.9 cm
Package 1 Width	27.2 cm
Package 1 Length	50.8 cm
Package 1 Weight	20.75 kg


Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------


Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)


[How we assess product sustainability >](#)

<div>Environmental footprint</div>	
Environmental Disclosure	Product Environmental Profile

Use Better

<div>Materials and Substances</div>	
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration

Use Again

<div>Repack and remanufacture</div>	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No