Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Symmetra PX Power Module, 10/16kW, 400V



SYPM10K16H

Overview

Presentation	A 16kW high efficiency power module for the Symmetra PX160kW & PX48kW. This power module is backward compatible with the SYPM10KH module and will autodetect to deliver only 10kW of power protection if installed in a PX80kW, 40KW or 20kW all-in-one.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V 400 V 3 phases
Rated power in W	16000 W
Rated power in VA	16000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Provided equipment	Installation guide

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage

Physical

Height	13.2 cm
Width	48.3 cm
Depth	70 cm
Net weight	28.5 kg
Mounting location	Front
USB compatible	No

Input

Network frequency	4070 Hz
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Input voltage limits	340477 V
Maximum input current	33 A
Max short time withstand current	30 kA

Input harmonic distortion	Less than 5 % for full load
Input Power Factor at Full Load	0.99

Output

Maximum configurable power in W	16000 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	Unlimited
UPS type	Double conversion online
Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
Output harmonic distortion	< 2% for 0 to 100% linear load and < 6% for full non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%

Conformance

Product certifications	CE
Standards	EN 50091-1
	EN 50091-3
	FCC part 15 class A
	VFI-SS-111

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	03333 ft
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 %
Storage altitude	0.00000000004572.0000000000 m
Acoustic level	63 dBA
Heat dissipation	2573 Btu/h
NEMA degree of protection	NEMA 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.5 cm
Package 1 Width	70 cm
Package 1 Length	59.5 cm
Package 1 Weight	31.55 kg

Contractual warranty

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

REACh Regulation REACh Declaration

Use Again

12 Mar 2025

○ Repack and remanufacture

Circularity Profile End of Life Information