Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





APC Symmetra RM 2-6kVA Power Module (2kVA)

SYPM2KU

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

- IVIGITT	
Main Input Voltage	200 V
	208 V
Product or component type	Power module
Main Output Voltage	200 V
	208 V
	230 V
Rated power in W	1400 W
Rated power in VA	2000 VA
Number of rack unit	0U
Number of cables	1
Provided equipment	Installation guide
Range of product	Symmetra Power Module

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Physical

Height	8.26 cm
Width	21.59 cm
Depth	54.61 cm
Net weight	7.73 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	155276 V

Output

Maximum configurable power in 1400 W

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.77 cm
Package 1 Width	35.56 cm
Package 1 Length	66.04 cm
Package 1 Weight	9.071 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

a	Environmental foot	:
Y)	Environmental toot	print

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

REACh Regulation REACh Declaration

Use Again

○ Repack and remanufacture

Circularity Profile End of Life Information

Take-back No